



5.6 Meter Earth Station Antenna

The ASC Signal 5.6 meter Ku-band and K-band earth station antenna features a uniquely formed dual reflector Gregorian system. This configuration coupled with close-tolerance manufacturing provide maximum durability with minimal maintenance.

In addition, the 5.6 meter Ku-band and K-band antenna features a tripod ground mount fabricated from hot-dipped galvanized steel to ensure extended product life. All structural components are covered with a three year warranty.

- Deep equipment enclosure for hub mount electronics
- Russian Homologation Certificate # OC/1-AO-136
- 3 year warranty on all structural components



SPECIFICATIONS

5.6 Meter Earth Station Antenna

Electrical Performance

	Ku-band 2-Port Linear Pol Feed		Ku-band 4-Port Linear Pol Feed		K-band 2-Port Linear Pol Feed		K-band 4-Port Linear Pol Feed	
	Receive	Transmit	Receive	Transmit	Receive	Transmit	Receive	Transmit
Frequency (GHz)	10.700-13.250	13.750-14.800	10.700-12.750	13.750-14.800	10.700-12.750	17.300-18.400	10.700-12.750	17.300-18.400
Antenna Gain at Output Flange (dBi ±0.2 dB) Frequency								
11.9500 GHz	55.50		55.10		55.50		55.10	
14.2500 GHz	57.00		56.70		N/A		N/A	
17.3000 GHz	N/A		N/A		57.90		57.50	
18.4000 GHz	N/A		N/A		58.40		58.00	
Antenna Noise Temperature (Clear Sky Conditions at 68°F (20°C))								
10° Elevation	49 K		71 K		69 K		85 K	
30° Elevation	38 K		60 K		55 K		71 K	
50° Elevation	35 K		57 K		50 K		66 K	
Cross Polarization								
On Axis	35 dB	35 dB	35 dB	35 dB	35 dB	35 dB	35 dB	35 dB
Within 1 dB Beamwidth	35 dB	35 dB	35 dB	35 dB	35 dB	35 dB	35 dB	35 dB
Axial Ratio	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
VSWR Performance	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1
Port-to-Port Isolation								
Rx to Rx	N/A		>35 dB		N/A		40 dB	
Tx to Rx	>40 dB		>85 dB		40 dB		85 dB	
Tx to Tx	N/A		>40 dB		N/A		40 dB	
Waveguide Interface Flange	WR75	WR75	Aluminum WR75	Aluminum WR75	WR62	WR75	WR62G	WR75
Tx Power Capacity	2000 W		2000 W		2000 W		2000 W	

Mechanical Performance

Optics Type	Dual Reflector, Gregorian	
Reflector Material	Precision Formed Aluminum	
Reflector Segments	16	
Mount Type	Tripod Mount	
Antenna Pointing Range	Elevation	5° Coarse, 85° Continuous
	Azimuth	180° Coarse, 120° Continuous
	Polarization	180° Coarse, 180° Continuous
Hub/Enclosure Dimensions	Diameter	1.32 m (52 in)
	Depth	1.17 m (46 in)

Environmental Performance

Operational Temperature	-40°C to 52°C (-40°F to 125°F)
Wind Loading (Survival)	200 km/h (125 mph) Any Position
Wind Loading (Operational)	with Motor 72 km/h (45 mph) with Gusts up to 105 km/h (65 mph)
	without Motor 72 km/h (45 mph) with Gusts up to 105 km/h (65 mph)
Rain	102 mm (4 in per hour)
Relative Humidity	100%
Shock and Vibration	As Encountered by Commercial Air, Rail and Truck
Atmospheric Conditions	As Encountered by Moderately Corrosive Coastal and Industrial Areas



ASC Signal Corporation
620 North Greenfield Parkway
Garner, NC 27529 USA

Telephone: +1-919-329-8700

Fax: +1-919-329-8701

Internet: www.ascsignal.com

All designs, specifications and availabilities of products and services presented in this bulletin are subject to change without notice.

ASC-ESA14

© 2007 ASC Signal Corporation